

UM-5SMD


Features

- compact
- surface mount
- extremely high stability
- extremely slow aging

Applications

- Bluetooth
- GPS / HDD
- WLAN PDA / Modem
- Pager

UM-5SMD



All dimensions are in millimeters.

Specifications

VIBRATION MODE:	fundamental / third overtone / fifth overtone
FREQUENCY TOLERANCE AT 25°C:	±10ppm ~ ±50ppm
LOADING CAPACITANCE:	10pF ~ 32pF or series
SHUNT CAPACITANCE:	7.0pF max.
EQUIVALENT SERIES RESISTANCE:	see Resistance Table
FREQUENCY VS. OPERATING TEMP:	see Frequency vs Operating Temp Table
DRIVE LEVEL:	10 • W ~ 1000 • W
INSULATION RESISTANCE:	500MΩmin / DC 100V
STORAGE TEMPERATURE RANGE:	-40°C ~ +85°C

Resistance Table (ESR)

Frequency Range(MHz):	UM-1 / SMD	UM-5 / SMD	Vibration mode
3.500+ ~ 4.000	200	-	fundamental
4.000+ ~ 5.000	150	-	fundamental
5.000+ ~ 10.000	60	-	fundamental
10.000+ ~ 15.000	40	60	fundamental
15.000+ ~ 30.000	30	35	fundamental
30.000+ ~ 50.000	45	50	third overtone
50.000+ ~ 100.000	60	60	third overtone
100.000+ ~ 160.000	80	90	fifth overtone

Frequency vs Operating Temp Table

Temp(°C)	PPM							
	±5	±7.5	±10	±15	±20	±30	±50	
0 ~ +50	*	*	*	*	*	*	*	
-10 ~ +60	*	*	*	*	*	*	*	
-20 ~ +70	*	*	*	*	*	*	*	
-30 ~ +80		*	*	*	*	*	*	
-40 ~ +85			*	*	*	*	*	